



AUTONOMOUS UNDERWATER GROUND VEHICLES (AUGVs)

SOFTWARE

// ROBOTIC SERVICES

OCEAN VEHICLES

BAYONET 250

Versatile Workhorse

Operating from the sea floor to the beachhead, Bayonet AUGVs travel through the harshest conditions where other systems cannot. The adaptability and strength of the B250 make it a favored option for operators seeking a reliable and efficient AUGV.





BAYONET 250

Technical Data

The B250 is the workhorse of the Bayonet series, striking an optimal balance between size, mobility, logistics, and payload capacity. Its robust design allows it to withstand harsher conditions and carry more extensive payloads than the B150. The B250 can be mobilized efficiently from a pickup truck, making it a versatile and practical choice for various missions. Its adaptability and strength make it a favored option for operators seeking a reliable and efficient AUGV.





Specifications subject to change without notice.

DIMENSIONS	48 in X 48 in X 12 in 15 inches from ground to deck
OPEN DECK SPACE	26 in X 12 in
WEIGHT (WITH BATTERIES)	390 lbs
BATTERY CAPACITY	2 kWh (standard) +2 kWh (extended)
RANGE (DRY / WET)	6 nmi / 8 nmi
DURATION	6 hrs (approximate)
DECK CAPACITY	200 lbs continuous 325 lbs peak
NAVIGATION POSITIONING	Greensea IQ OPENINS
COMMAND & CONTROL SOFTWARE	OPENSEA Greensea IQ Workspace user interface

// BAYONET 250 FEATURES

- Amphibious / Surf Zone
- 100 meter depth rated
- Modular components for logistics
- Large deck space for payload / mission flexibility
- Advanced Navigation Fiber Optic Gyroscope (FOG)
- Field swappable battery packs one per pontoon

// INTERFACE / ELECTRICAL

- 24VDC, 250 Watts
- Gigabit Ethernet 6 ports

SENSOR PACKAGES

Standard:

- Depth Sensor Keller Scientific
- Camera Sidus SS400IP
- Forward Looking Sonar Oculus 750, 1200
- GPS Ublox / Advanced Navigation
- IP Radio 70Mbs (approximate), LOS 100 meters

Optional:

- ACOMMS Benthos, Oceancomm
- RTK GPS Trimble R12
- DVL Nortek



